

HOOK UP WIRE

PVC Insulated UL Hook Up Wire

To UL Style 1007/1569 & CSA Type TR-64 (Dual Rated)



Maximum temperature 105°C

MASON Part No.	AWG	No. & Size of Strands	Nominal Insulation Thickness	Nominal O.D.	Nominal D.C. Resistance at 20°C	Current Rating (Amps)	Reel Size
UL100728	28	7 x 0.12 mm	0.38 mm	1.25 mm	238.90 Ω/km	2	1000m
UL100726	26	7 x 0.16 mm	0.38 mm	1.30 mm	148.94 Ω/km	3	1000m
UL100724	24	11 x 0.16 mm	0.38 mm	1.50 mm	93.25 Ω/km	4	1000m
UL100722	22	17 x 0.16 mm	0.38 mm	1.60 mm	55.00 Ω/km	6	1000m
UL100720	20	10 x 0.25 mm	0.38 mm	1.80 mm	40.02 Ω/km	9	1000m
UL100718	18	16 x 0.25 mm	0.38 mm	2.10 mm	21.80 Ω/km	14	500m

To UL Style 1061 & CSA Type AWM

Maximum temperature 80°C

MASON Part No.	AWG	No. & Size of Strands	Nominal Insulation Thickness	Nominal O.D.	Nominal D.C. Resistance at 20°C	Current Rating (Amps)	Reel Size
UL106128	28	7 x 0.12 mm	0.26 mm	0.90 mm	238.90 Ω/km	1	1000m
UL106126	26	7 x 0.16 mm	0.26 mm	1.00 mm	139.00 Ω/km	2	1000m
UL106124	24	7 x 0.20 mm	0.27 mm	1.15 mm	93.25 Ω/km	3	1000m
UL106122	22	7 x 0.25 mm	0.26 mm	1.28 mm	55.00 Ω/km	6	1000m

APPLICATION

Stranded UL and CSA certified Hook Up Wire is used for the internal wiring of electrical and electronic equipment.

SPECIFICATION

Voltage rating 300 volts

Tinned annealed copper conductors

Insulated with heat resistant PVC

Conforms with the UL VW-1 vertical wire flame test

STANDARD COLOURS

Black, Blue, Brown, Green, Grey, Orange, Pink, Red, Violet, White, Yellow, Green / Yellow

Other two and three colour options are available upon request.

Please contact our Sales Office for details of colours available in particular sizes / lengths.